



PCT

 CITED BY APPLICANT
 WORLD INTELLECTUAL PROPERTY ORGANIZATION
 International Bureau


INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : G06T 11/00	A1	(11) International Publication Number: WO 00/26857 (43) International Publication Date: 11 May 2000 (11.05.00)
(21) International Application Number: PCT/US99/23981 (22) International Filing Date: 27 October 1999 (27.10.99) (30) Priority Data: 09/182,070 29 October 1998 (29.10.98) US (71) Applicant: PIXAR ANIMATION STUDIOS [US/US]; 1001 West Cutting Boulevard, Richmond, CA 94804 (US). (72) Inventor: RAO, Arun; 498 Chaucer Circle, San Ramon, CA 94583 (US). (74) Agent: DONNELLY, Darren; McCutchen, Doyle, Brown & Enersen, LLP, Three Embarcadero Center, San Francisco, CA 94111 (US).	(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published With international search report.	

(54) Title: COLOR MANAGEMENT SYSTEM

(57) Abstract

A system for efficiently converting computer graphics images to film images with accurate color management is described. The system involves the creation of a direct mapping of chromaticity and intensity data from the values used to generate images on a computer monitor to the values used to display the images on projected motion picture film.

REF. 1 DOCKET P4040223

CORRES. COUNTRY: _____

COUNTRY: PCT

BEST AVAILABLE COPY

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CJ	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

Color Management System

Field of the Invention

The present invention relates to digital film production and, more particularly, to techniques for efficiently and accurately converting color computer graphics images to film images.

Background of the Invention

When creating a computer-animated motion picture, the animation team uses computers to create, view, and manipulate images used in the motion picture. The animation team makes judgments concerning the desired appearance of the images, and manipulates the images, based on how the images appear when displayed on the computer monitors.

The motion picture ultimately will be displayed to a theater audience using conventional motion picture film and projectors. Accordingly, the image data stored on computer must be converted into film images for projection in a theater.

Digital film recorders are used to convert the original, computer-generated images created by the animation team into images on photosensitive motion picture film. Conventional digital film recorders use a light source (such as a laser) to expose each frame of the film as necessary to produce the desired image in the frame. The film is then advanced to the next frame and the process is repeated. When a strip of film has been recorded, it is sent to a laboratory for development into a color negative and, ultimately, a positive print.

To create high quality computer-generated films, film producers must make certain that the ultimate appearance of the motion picture that is projected and viewed by an audience matches the appearance desired by the creative team. The color of each location on the exposed film should match, as closely as possible, the color of the corresponding picture element ("pixel") on the display device used by the artist who created the image. To produce a visually accurate color image using a digital film recorder, the locations on a frame of film that correspond to each pixel of an image must be exposed precisely. The calculation of this exposure (for each primary component, red, green and blue) depends on the nature of the source and the characteristics of the film used.

Producing a film image that corresponds visually to the original image created and/or stored on a computer is not as straightforward as it might initially appear. Difficulties arise because the color densities produced on a film generally do not correspond linearly to the RGB color values that displayed on the computer monitor. The color densities actually
5 produced on the film are affected by a variety of factors, including chemical characteristics of the film itself. For example, due to chemical characteristics of the film, the density of a particular color produced on the film by a beam of light generally will not vary linearly with the intensity of light used to expose the film for a given time duration. Temperature, film type, characteristics of a light source used in the recorder and noise generated by the system
10 can affect the color density values actually produced.

Similarly, the stored value used to produce a particular measured density for one color component in a neutral tone generally will not produce the same measured density in color. For example, if the combination of red, green and blue code values X1, Y1 and Z1 produce measured red, green and blue densities R1, G1, and B1, then the red code value X1 used in
15 combination with different green and blue code values (*i.e.*, Y2 and Z2) generally will not produce the density R1.

The monitor itself has nonlinear characteristics. The well-known gamma correction process is used to correct for nonlinearities in specific monitors. Nevertheless, even a monitor's characteristics tend to degrade over time. Monitors operate in RGB color spaces in
20 which colors are created by mixing proportions of Red, Green and Blue light. Monitors from different suppliers may use different phosphors and an individual monitor itself will age. This is equivalent to different or gradually changing color spaces. All of these problems and complexities suggest to those skilled in the field the complex color management schemes necessary.

25 Another problem is that the film cannot reproduce all the colors reproducible on the monitor (the converse is also true, but less important since we're only trying to mimic the monitor). This phenomenon is referred to as "gamut mismatch," and treating such cases in a consistent manner is difficult. One approach would be to take all the colors that are outside

the film's gamut and map them to the closest (in some sense) point on the surface of the film's gamut. Colors which are inside the gamut to start with would be left alone. This approach, however, results in abrupt color changes which result in banding artifacts in the final image.

5 Industry literature generally teaches that solutions to the above-described problems must be complex. "Historically, managing color has been a very time consuming and costly process in the printing, prepress, and film industries." Has & Newman, *Color Management: Current Practice and The Adoption of a New Standard*. "Color is an immensely complex subject, one that draws on concepts and results from physics, physiology, psychology, art, and
10 graphic design. The color of an object depends not only on the object itself, but also on the light source illuminating it, on the color of the surrounding area, and on the human visual system." See Foley and Van Dam, *Computer Graphics Principles and Practice* (Second Edition 1996).

 In accordance with such theory, conventional approaches to producing color images
15 on film that match the originally created computer graphics images have been complex. For example, some conventional approaches involve the use of complex models of the film development process to change the primary color component values derived from the computer graphics images into values that will produce a similar visual result on film. Other conventional approaches arrive (by trial and error and much manual tweaking) at a transfer
20 curve for each channel such that the colors on the screen look acceptable. Such methods do not allow for fine-grained, color-by-color matching. In any event, it is generally understood that brightness, or intensity, values that are used in connection with the display of images on a computer screen cannot be converted to the film media, as they are irrelevant to the visual perception of the film in the theater environment. In the theater environment, so the
25 reasoning goes, the psychophysical perception of various colors by the audience is affected by the darkness of the theater and numerous other subtle factors that are difficult or impossible to account for in advance. It is generally understood that the intensity value of each color component must be determined by visual inspection in the new medium (*i.e.*, the film

projected in a theater environment).

Conventional approaches to dealing with the above matter typically address the reproduction of color on print media, which cannot reproduce colors as well as monitors can. Most importantly, the dynamic range (ratio of maximum to minimum brightness values) is substantially lower than that of monitors. Much attention is therefore focused on the problem of compressing the dynamic range. Film, on the other hand, offers a dynamic range that is comparable (or even larger) than that of monitors, an issue which has not been addressed adequately in the literature.

Efficient and accurate techniques for converting color computer graphics images to film images would be highly desirable.

Summary of the Invention

The present invention involves a color management system for efficiently and accurately converting computer graphics images to film images. In certain embodiments, the system includes at least three steps: determining an RGB-to-XYZ mapping for the monitor; measuring the RGB-to-XYZ mapping applicable to the film recording; and creating an RGB-to-RGB mapping for operating on the image colors displayed on the monitor to create accurate color densities on the film. In many embodiments, each mapping uses color spaces that incorporate both chromaticity and intensity data for each color component.

As will be understood by those skilled in the art based on the present disclosure, a wide variety of embodiments of the present invention exist and fall within the scope of the claims set forth herein. The scope of the present invention is defined by the claims.

Brief Description of the Figures

FIG. 1 shows one embodiment of a digital film production system in connection with which color management according to the present invention is useful.

FIG. 2 shows a series of steps for performing color management according to the present invention.

Detailed Description of Preferred Embodiment(s)

A diagram of one example of a digital film production system for recording computer-

generated images onto motion picture film is illustrated at 10 in FIG. 1. Embodiments of the present invention are useful when performing color management in connection with any conventional film production system, including film production system 10.

In FIG. 1, computer system 102 preferably is a workstation, although any
5 conventional computer system may be used. In addition to other conventional components, computer system 102 comprises a conventional monitor 104 used to view images during the film production process. Creative personnel 101 create, manipulate and modify images on computer system 102, viewing the images on monitor 104 and basing their creative judgements regarding color in part on the appearance of the images when displayed on
10 monitor 104.

After images have been created and modified using computer system 102, the images are printed onto motion picture film using a film recorder 106. Film recorder 106 is a conventional digital film recorder, preferably a laser recorder that exposes film according to specified RGB values. It will be appreciated by those skilled in the art that the present
15 invention is also useful in connection with CRT and EBR (electron beam) recorders.

The recorded filmstrips are then sent to a photographic laboratory ("lab") 108 for processing. In a conventional manner, the filmstrips are developed to create a negative, which is used to create a positive filmstrip 110.

Filmstrip 110 is then viewed using a conventional motion picture film projector 112.

20 In the past, in order to address the problem of color management with respect to chromaticity alone, film producers have created a look-up table 113 to convert the color data stored on the computer into color data that can be used by film recorder 106 to expose a strip of film and used complicated models 115 to account for nonlinearities during laboratory processing. The film has then been viewed using projector 112 to determine appropriate
25 intensity levels for each color component for a given motion picture. Certain embodiments of the present invention eliminate the need for such complexity.

In accordance with the present invention, color management is performed in connection with converting the computer graphics images created on computer system 102 to

the film images printed on filmstrip 110 that are projected for a viewing audience using projector 112. Certain embodiments of the present invention look at the system "end-to-end," from the computer graphics image input to the projected image output, and involve the creation of a monitor-to-film ("MFM") mapping 120 for the system using color spaces that incorporate both chromaticity and intensity data for each color component.

Color management in accordance with certain embodiments of the present invention involves three main steps, which need not be performed in the order listed below. The first step (step 202) is to determine a first RGB-to-XYZ mapping applicable to the monitor. This first RGB-to-XYZ mapping preferably uses color spaces incorporating both chromaticity and intensity data for each color component.

The XYZ color space is a way of representing color information in device independent terms in a manner that incorporates both intensity and chromaticity data for each color component. The basis of device independent color representation is usually the Commission Internationale De L'Eclairage ("CIE") XYZ space. It will be apparent to those skilled in the art, based on the present disclosure, that color spaces other than the CIE XYZ space may be used as the XYZ color space for purposes of the present invention.

Certain embodiments of the present invention use an adaptation of the ATD space proposed by Lee Guth. Other embodiments use other perceptually uniform spaces, like CIELab or CIELuv. Those skilled in the art will recognize that the color space in which measurements are made (XYZ) and the computation space (ATD, preferably) are distinct. As will be apparent to those skilled in the art, the choice of computation space is important for the treatment of out-of-gamut colors.

The second step (step 204) is to make appropriate measurements to create a second RGB-to-XYZ mapping applicable to the film recording. The second RGB-to-XYZ mapping preferably uses color spaces incorporating both chromaticity and intensity data for each color component. To accomplish this objective, one records a strip of 1000 frames of flat color patches calculated to span the entire RGB space (10 steps along each axis). Next, one projects these frames on to a screen, and points a spectrophotometer (preferably, a

Spectrascan PR-650) at the center of the patch. One reads the spectrum (101 samples in 4 nm steps from 380 to 780 nm), corrects it for the projector bulb spectrum (i.e. divide by test projector spectrum and multiply by theater projector spectrum), and converts to an XYZ triple by integration. (This integration process is well-defined by CIE). One thus obtains a set of 1000 readings, where each reading consists of a pair of triples: the RGB triple used to record the patch, and the resulting XYZ triple. The XYZ values are converted finally to the internal computation space (ATD).

The third step (step 206) is to create an RGB-to-RGB mapping, preferably incorporating both chromaticity and intensity data for each color component, for operating on the image colors displayed on the monitor to create accurate color densities on the projected film.

The present invention also addresses the issue of gamut mismatch. The basic idea is to "pull in" colors along a line connecting the gray (or achromatic) axis and the color to be reproduced. This line intersects both film and monitor gamut surfaces. If the monitor surface intersection is nearer than the film surface intersection, one need do nothing, because all colors along this line are reproducible on film. If not, one smoothly (using a quadratic function) remaps colors along the line such that the monitor surface intersection color is mapped to the film surface intersection color.

Although the present invention has been described in connection with certain specific embodiments, it will be clear to those skilled in the art that the inventive features of the present invention are applicable to other embodiments as well. All of such embodiments are intended to fall within the scope of the present invention.

Based on the present disclosure, those skilled in the art will understand that the present invention has broad applicability in connection with the use of computers during the production or processing of film. For example, embodiments of the present invention are useful in connection with computer generation of entirely synthetic images for 2D or 3D animation. Embodiments of the present invention are also useful in connection with the use of computers to modify live action film, either for touch up or to add special effects.

Claims

- 1 1. A color management system for converting computer graphics images to film
2 images, the computer graphics images being displayed on and manipulated using a computer
3 monitor, the film images being recorded on film using a digital film recorder for exposing the
4 film with light at predetermined intensity levels corresponding to specified RGB values,
5 comprising the steps of:
6 determining a first RGB-to-XYZ mapping applicable to the monitor, said first RGB-
7 to-XYZ mapping using color spaces incorporating chromaticity and intensity data for each
8 color component;
9 measuring a second RGB-to-XYZ mapping applicable to the film recording, said
10 second RGB-to-XYZ mapping using color spaces incorporating chromaticity and intensity
11 data for each color component; and
12 creating an RGB-to-RGB mapping, incorporating chromaticity and intensity data for
13 each color component, for operating on the image colors displayed on the monitor to create
14 accurate color densities on the film.
- 1 2. A method for converting computer graphics images displayed on a monitor to film
2 images, comprising the steps of:
3 determining an RGB-to-XYZ mapping incorporating chromaticity and intensity data
4 for the monitor;
5 determining an RGB-to-XYZ mapping incorporating chromaticity and intensity data
6 for a film recording; and
7 generating an RGB-to-RGB mapping, incorporating chromaticity and intensity data
8 for at least one color component, for converting the image colors displayed on the monitor to
9 color densities on the film.
- 1 3. The method of Claim 2, wherein the RGB-to-XYZ mapping for the monitor
2 incorporates chromaticity and intensity data for each color component.

1 4. The method of Claim 2, wherein the RGB-to-XYZ mapping for the film recording
2 incorporates chromaticity and intensity data for each color component.

1 5. The method of Claim 2, wherein the RGB-to-RGB mapping incorporates
2 chromaticity and intensity data for each color component.

1 6. A color management system for converting computer graphics images to film
2 images, the computer graphics images being displayed on and manipulated using a computer
3 monitor, the film images being recorded on film using a digital film recorder for exposing the
4 film with light at predetermined intensity levels corresponding to specified RGB values,
5 comprising:

6 a first RGB-to-XYZ mapping applicable to the monitor, said first RGB-to-XYZ
7 mapping using color spaces incorporating chromaticity and intensity data for each color
8 component;

9 a second RGB-to-XYZ mapping applicable to the film recording, said second RGB-
10 to-XYZ mapping using color spaces incorporating chromaticity and intensity data for each
11 color component; and

12 an RGB-to-RGB mapping, incorporating chromaticity and intensity data for each
13 color component, for operating on the image colors displayed on the monitor to create
14 accurate color densities on the film.

1 7. A color management system for converting color computer graphics images to
2 color film images, comprising:

3 a computer system having a monitor for displaying the computer graphics images;
4 an RGB-to-XYZ mapping, incorporating chromaticity and intensity data, for the
5 monitor;

6 an RGB-to-XYZ mapping, incorporating chromaticity and intensity data, applicable to
7 recording the film images;

8 an RGB-to-RGB mapping, incorporating chromaticity and intensity data, for operating
9 on the images displayed on the monitor to create color components for recording the film
10 images

1 8. The system of Claim 7, wherein the computer system comprises a work station.

1 9. The computer system of Claim 7, further comprising a digital film recorder for
2 exposing film with the film images using light at predetermined intensity levels
3 corresponding to specified RGB values.

1 10. The computer system of Claim 7, wherein the RGB-to-XYZ mapping for the
2 monitor incorporates chromaticity and intensity data for each color component.

1 11. The computer system of Claim 7, wherein the RGB-to-XYZ mapping for recording
2 the film images incorporates chromaticity and intensity data for each color component.

1 12. The computer system of Claim 7, wherein the RGB-to-RGB mapping
2 incorporates chromaticity and intensity data for each color component.




FIG. 1

2 / 2




FIG. 2

INTERNATIONAL SEARCH REPORT

International Application No.

PCT/US 99/23981

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 G06T11/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 G06T

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	MACDONALD L W: "Developments in colour management systems" DISPLAYS,GB,ELSEVIER SCIENCE PUBLISHERS BV., BARKING, vol. 16, no. 4, 1 May 1996 (1996-05-01), pages 203-211, XP004032522 ISSN: 0141-9382 the whole document	1-12
X	US 5 754 184 A (RING STUART FREDERICK ET AL) 19 May 1998 (1998-05-19) abstract; claims 1-7 column 5, paragraphs 1-3 column 8, line 35 - line 44	1-12

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

28 January 2000

Date of mailing of the international search report

08/02/2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Filloy García, E

INTERNATIONAL SEARCH REPORT

Int. Appl. No.
PCT/US 99/23981

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No
P,X	<p>RAMAMURTHY A ET AL: "ACHIEVING COLOR MATCH BETWEEN SCANNER, MONITOR, AND FILM: A COLOR MANAGEMENT IMPLEMENTATION FOR FEATURE ANIMATION"</p> <p>SMPTE JOURNAL,US,SMPTE INC. SCARSDALE, N.Y,</p> <p>vol. 108, no. 6, June 1999 (1999-06), pages 363-373, XP000831862</p> <p>ISSN: 0036-1682</p> <p>page 364 -page 366; figure 1</p> <p style="text-align: center;">---</p>	1-12
Y	<p>WO 95 31794 A (APPLE COMPUTERS INC ;SWEN IUE NA STEVE (US); STOKES MICHAEL D (US))</p> <p>23 November 1995 (1995-11-23)</p> <p>page 9, line 3 - line 13; figure 7</p> <p>page 17, paragraphs 3,4</p> <p style="text-align: center;">---</p>	1-12
Y	<p>EP 0 814 603 A (KONISHIROKU PHOTO IND)</p> <p>29 December 1997 (1997-12-29)</p> <p>claims 1,7-9,12,15; figure 1</p> <p>page 12, line 41 -page 13, line 2</p> <p style="text-align: center;">---</p>	1-12
A	<p>K. JIN-SEO ET AL: "Development of Color Management System Prototype"</p> <p>PROCEEDINGS OF THE 1998 IEEE INTERNATIONAL CONFERENCE ON SYSTEMS, MAN, AND CYBERNETICS,</p> <p>vol. 3, 11 - 14 October 1998, pages 2529-2532, XP000874180</p> <p>San Diego, USA</p> <p>abstract; page 2530, section 3</p> <p style="text-align: center;">---</p>	1-12
A	<p>US 4 979 032 A (GIORGIANNI EDWARD J ET AL) 18 December 1990 (1990-12-18)</p> <p>abstract; figure 1</p> <p style="text-align: center;">---</p>	1-12
A	<p>EP 0 637 731 A (TOYOTA MOTOR CO LTD)</p> <p>8 February 1995 (1995-02-08)</p> <p>abstract; claims 1-3</p> <p style="text-align: center;">-----</p>	1-12

INTERNATIONAL SEARCH REPORT

information on patent family members

Inter national Application No

PCT/US 99/23981

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5754184 A	19-05-1998	NONE	
WO 9531794 A	23-11-1995	AU 2640095 A	05-12-1995
EP 0814603 A	29-12-1997	JP 10075377 A	17-03-1998
		US 5966505 A	12-10-1999
US 4979032 A	18-12-1990	NONE	
EP 0637731 A	08-02-1995	JP 7050760 A	21-02-1995
		JP 2921365 B	19-07-1999
		JP 7150081 A	13-06-1995
		DE 69414323 D	10-12-1998
		DE 69414323 T	27-05-1999
		EP 0822396 A	04-02-1998
		US 5590251 A	31-12-1996

THIS PAGE BLANK (USPTO)



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : G06T 11/00	A1	(11) International Publication Number: WO 00/26857 (43) International Publication Date: 11 May 2000 (11.05.00)
(21) International Application Number: PCT/US99/23981 (22) International Filing Date: 27 October 1999 (27.10.99) (30) Priority Data: 09/182,070 29 October 1998 (29.10.98) US (71) Applicant: PIXAR ANIMATION STUDIOS [US/US]; 1001 West Cutting Boulevard, Richmond, CA 94804 (US). (72) Inventor: RAO, Arun; 498 Chaucer Circle, San Ramon, CA 94583 (US). (74) Agent: DONNELLY, Darren; McCutchen, Doyle, Brown & Enersen, LLP, Three Embarcadero Center, San Francisco, CA 94111 (US).		(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i>
(54) Title: COLOR MANAGEMENT SYSTEM (57) Abstract <p>A system for efficiently converting computer graphics images to film images with accurate color management is described. The system involves the creation of a direct mapping of chromaticity and intensity data from the values used to generate images on a computer monitor to the values used to display the images on projected motion picture film.</p> <div style="text-align: center;"> <pre> graph TD 202[Create First RGB-XYZ Mapping For Monitor 202] <--> 204[Create Second RGB-XYZ Mapping For Recording On Film 204] 204 <--> 206[Create RGB-RGB Monitor-To-Film ("MFM") Mapping 206] </pre> </div>		

*(Referred to in PCT Gazette No. 39/2000, Section II)

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

Color Management System

Field of the Invention

The present invention relates to digital film production and, more particularly, to techniques for efficiently and accurately converting color computer graphics images to film images.

Background of the Invention

When creating a computer-animated motion picture, the animation team uses computers to create, view, and manipulate images used in the motion picture. The animation team makes judgments concerning the desired appearance of the images, and manipulates the images, based on how the images appear when displayed on the computer monitors.

The motion picture ultimately will be displayed to a theater audience using conventional motion picture film and projectors. Accordingly, the image data stored on computer must be converted into film images for projection in a theater.

Digital film recorders are used to convert the original, computer-generated images created by the animation team into images on photosensitive motion picture film. Conventional digital film recorders use a light source (such as a laser) to expose each frame of the film as necessary to produce the desired image in the frame. The film is then advanced to the next frame and the process is repeated. When a strip of film has been recorded, it is sent to a laboratory for development into a color negative and, ultimately, a positive print.

To create high quality computer-generated films, film producers must make certain that the ultimate appearance of the motion picture that is projected and viewed by an audience matches the appearance desired by the creative team. The color of each location on the exposed film should match, as closely as possible, the color of the corresponding picture element ("pixel") on the display device used by the artist who created the image. To produce a visually accurate color image using a digital film recorder, the locations on a frame of film that correspond to each pixel of an image must be exposed precisely. The calculation of this exposure (for each primary component, red, green and blue) depends on the nature of the source and the characteristics of the film used.

Producing a film image that corresponds visually to the original image created and/or stored on a computer is not as straightforward as it might initially appear. Difficulties arise because the color densities produced on a film generally do not correspond linearly to the RGB color values that displayed on the computer monitor. The color densities actually produced on the film are affected by a variety of factors, including chemical characteristics of the film itself. For example, due to chemical characteristics of the film, the density of a particular color produced on the film by a beam of light generally will not vary linearly with the intensity of light used to expose the film for a given time duration. Temperature, film type, characteristics of a light source used in the recorder and noise generated by the system can affect the color density values actually produced.

Similarly, the stored value used to produce a particular measured density for one color component in a neutral tone generally will not produce the same measured density in color. For example, if the combination of red, green and blue code values $X1$, $Y1$ and $Z1$ produce measured red, green and blue densities $R1$, $G1$, and $B1$, then the red code value $X1$ used in combination with different green and blue code values (*i.e.*, $Y2$ and $Z2$) generally will not produce the density $R1$.

The monitor itself has nonlinear characteristics. The well-known gamma correction process is used to correct for nonlinearities in specific monitors. Nevertheless, even a monitor's characteristics tend to degrade over time. Monitors operate in RGB color spaces in which colors are created by mixing proportions of Red, Green and Blue light. Monitors from different suppliers may use different phosphors and an individual monitor itself will age. This is equivalent to different or gradually changing color spaces. All of these problems and complexities suggest to those skilled in the field the complex color management schemes necessary.

Another problem is that the film cannot reproduce all the colors reproducible on the monitor (the converse is also true, but less important since we're only trying to mimic the monitor). This phenomenon is referred to as "gamut mismatch," and treating such cases in a consistent manner is difficult. One approach would be to take all the colors that are outside

the film's gamut and map them to the closest (in some sense) point on the surface of the film's gamut. Colors which are inside the gamut to start with would be left alone. This approach, however, results in abrupt color changes which result in banding artifacts in the final image.

5 Industry literature generally teaches that solutions to the above-described problems must be complex. "Historically, managing color has been a very time consuming and costly process in the printing, prepress, and film industries." Has & Newman, *Color Management: Current Practice and The Adoption of a New Standard*. . "Color is an immensely complex subject, one that draws on concepts and results from physics, physiology, psychology, art, and
10 graphic design. The color of an object depends not only on the object itself, but also on the light source illuminating it, on the color of the surrounding area, and on the human visual system." See Foley and Van Dam, *Computer Graphics Principles and Practice* (Second Edition 1996).

 In accordance with such theory, conventional approaches to producing color images
15 on film that match the originally created computer graphics images have been complex. For example, some conventional approaches involve the use of complex models of the film development process to change the primary color component values derived from the computer graphics images into values that will produce a similar visual result on film. Other conventional approaches arrive (by trial and error and much manual tweaking) at a transfer
20 curve for each channel such that the colors on the screen look acceptable. Such methods do not allow for fine-grained, color-by-color matching. In any event, it is generally understood that brightness, or intensity, values that are used in connection with the display of images on a computer screen cannot be converted to the film media, as they are irrelevant to the visual perception of the film in the theater environment. In the theater environment, so the
25 reasoning goes, the psychophysical perception of various colors by the audience is affected by the darkness of the theater and numerous other subtle factors that are difficult or impossible to account for in advance. It is generally understood that the intensity value of each color component must be determined by visual inspection in the new medium (*i.e.*, the film

projected in a theater environment).

Conventional approaches to dealing with the above matter typically address the reproduction of color on print media, which cannot reproduce colors as well as monitors can. Most importantly, the dynamic range (ratio of maximum to minimum brightness values) is substantially lower than that of monitors. Much attention is therefore focused on the problem of compressing the dynamic range. Film, on the other hand, offers a dynamic range that is comparable (or even larger) than that of monitors, an issue which has not been addressed adequately in the literature.

Efficient and accurate techniques for converting color computer graphics images to film images would be highly desirable.

Summary of the Invention

The present invention involves a color management system for efficiently and accurately converting computer graphics images to film images. In certain embodiments, the system includes at least three steps: determining an RGB-to-XYZ mapping for the monitor; measuring the RGB-to-XYZ mapping applicable to the film recording; and creating an RGB-to-RGB mapping for operating on the image colors displayed on the monitor to create accurate color densities on the film. In many embodiments, each mapping uses color spaces that incorporate both chromaticity and intensity data for each color component.

As will be understood by those skilled in the art based on the present disclosure, a wide variety of embodiments of the present invention exist and fall within the scope of the claims set forth herein. The scope of the present invention is defined by the claims.

Brief Description of the Figures

FIG. 1 shows one embodiment of a digital film production system in connection with which color management according to the present invention is useful.

FIG. 2 shows a series of steps for performing color management according to the present invention.

Detailed Description of Preferred Embodiment(s)

A diagram of one example of a digital film production system for recording computer-

generated images onto motion picture film is illustrated at 10 in FIG. 1. Embodiments of the present invention are useful when performing color management in connection with any conventional film production system, including film production system 10.

In FIG. 1, computer system 102 preferably is a workstation, although any
5 conventional computer system may be used. In addition to other conventional components, computer system 102 comprises a conventional monitor 104 used to view images during the film production process. Creative personnel 101 create, manipulate and modify images on computer system 102, viewing the images on monitor 104 and basing their creative
10 judgements regarding color in part on the appearance of the images when displayed on monitor 104.

After images have been created and modified using computer system 102, the images are printed onto motion picture film using a film recorder 106. Film recorder 106 is a conventional digital film recorder, preferably a laser recorder that exposes film according to specified RGB values. It will be appreciated by those skilled in the art that the present
15 invention is also useful in connection with CRT and EBR (electron beam) recorders.

The recorded filmstrips are then sent to a photographic laboratory ("lab") 108 for processing. In a conventional manner, the filmstrips are developed to create a negative, which is used to create a positive filmstrip 110.

Filmstrip 110 is then viewed using a conventional motion picture film projector 112.

20 In the past, in order to address the problem of color management with respect to chromaticity alone, film producers have created a look-up table 113 to convert the color data stored on the computer into color data that can be used by film recorder 106 to expose a strip of film and used complicated models 115 to account for nonlinearities during laboratory processing. The film has then been viewed using projector 112 to determine appropriate
25 intensity levels for each color component for a given motion picture. Certain embodiments of the present invention eliminate the need for such complexity.

In accordance with the present invention, color management is performed in connection with converting the computer graphics images created on computer system 102 to

the film images printed on filmstrip 110 that are projected for a viewing audience using projector 112. Certain embodiments of the present invention look at the system “end-to-end,” from the computer graphics image input to the projected image output, and involve the creation of a monitor-to-film (“MFM”) mapping 120 for the system using color spaces that incorporate both chromaticity and intensity data for each color component.

Color management in accordance with certain embodiments of the present invention involves three main steps, which need not be performed in the order listed below. The first step (step 202) is to determine a first RGB-to-XYZ mapping applicable to the monitor. This first RGB-to-XYZ mapping preferably uses color spaces incorporating both chromaticity and intensity data for each color component.

The XYZ color space is a way of representing color information in device independent terms in a manner that incorporates both intensity and chromaticity data for each color component. The basis of device independent color representation is usually the Commission Internationale De L'Eclairage (“CIE”) XYZ space. It will be apparent to those skilled in the art, based on the present disclosure, that color spaces other than the CIE XYZ space may be used as the XYZ color space for purposes of the present invention.

Certain embodiments of the present invention use an adaptation of the ATD space proposed by Lee Guth. Other embodiments use other perceptually uniform spaces, like CIELab or CIELuv. Those skilled in the art will recognize that the color space in which measurements are made (XYZ) and the computation space (ATD, preferably) are distinct. As will be apparent to those skilled in the art, the choice of computation space is important for the treatment of out-of-gamut colors.

The second step (step 204) is to make appropriate measurements to create a second RGB-to-XYZ mapping applicable to the film recording. The second RGB-to-XYZ mapping preferably uses color spaces incorporating both chromaticity and intensity data for each color component. To accomplish this objective, one records a strip of 1000 frames of flat color patches calculated to span the entire RGB space (10 steps along each axis). Next, one projects these frames on to a screen, and points a spectrophotometer (preferably, a

Spectrascan PR-650) at the center of the patch. One reads the spectrum (101 samples in 4 nm steps from 380 to 780 nm), corrects it for the projector bulb spectrum (i.e. divide by test projector spectrum and multiply by theater projector spectrum), and converts to an XYZ triple by integration. (This integration process is well-defined by CIE). One thus obtains a set of
5 1000 readings, where each reading consists of a pair of triples: the RGB triple used to record the patch, and the resulting XYZ triple. The XYZ values are converted finally to the internal computation space (ATD).

The third step (step 206) is to create an RGB-to-ATD mapping, preferably incorporating both chromaticity and intensity data for each color component, for operating on
10 the image colors displayed on the monitor to create accurate color densities on the projected film.

The present invention also addresses the issue of gamut mismatch. The basic idea is to "pull in" colors along a line connecting the gray (or achromatic) axis and the color to be reproduced. This line intersects both film and monitor gamut surfaces. If the monitor surface
15 intersection is nearer than the film surface intersection, one need do nothing, because all colors along this line are reproducible on film. If not, one smoothly (using a quadratic function) remaps colors along the line such that the monitor surface intersection color is mapped to the film surface intersection color.

Although the present invention has been described in connection with certain specific
20 embodiments, it will be clear to those skilled in the art that the inventive features of the present invention are applicable to other embodiments as well. All of such embodiments are intended to fall within the scope of the present invention.

Based on the present disclosure, those skilled in the art will understand that the present invention has broad applicability in connection with the use of computers during the
25 production or processing of film. For example, embodiments of the present invention are useful in connection with computer generation of entirely synthetic images for 2D or 3D animation. Embodiments of the present invention are also useful in connection with the use of computers to modify live action film, either for touch up or to add special effects.

Claims

- 1 1. A color management system for converting computer graphics images to film
2 images, the computer graphics images being displayed on and manipulated using a computer
3 monitor, the film images being recorded on film using a digital film recorder for exposing the
4 film with light at predetermined intensity levels corresponding to specified RGB values,
5 comprising the steps of:
6 determining a first RGB-to-XYZ mapping applicable to the monitor, said first RGB-
7 to-XYZ mapping using color spaces incorporating chromaticity and intensity data for each
8 color component;
9 measuring a second RGB-to-XYZ mapping applicable to the film recording, said
10 second RGB-to-XYZ mapping using color spaces incorporating chromaticity and intensity
11 data for each color component; and
12 creating an RGB-to-RGB mapping, incorporating chromaticity and intensity data for
13 each color component, for operating on the image colors displayed on the monitor to create
14 accurate color densities on the film.
- 1 2. A method for converting computer graphics images displayed on a monitor to film
2 images, comprising the steps of:
3 determining an RGB-to-XYZ mapping incorporating chromaticity and intensity data
4 for the monitor;
5 determining an RGB-to-XYZ mapping incorporating chromaticity and intensity data
6 for a film recording; and
7 generating an RGB-to-RGB mapping, incorporating chromaticity and intensity data
8 for at least one color component, for converting the image colors displayed on the monitor to
9 color densities on the film.
- 1 3. The method of Claim 2, wherein the RGB-to-XYZ mapping for the monitor
2 incorporates chromaticity and intensity data for each color component.

1 4. The method of Claim 2, wherein the RGB-to-XYZ mapping for the film recording
2 incorporates chromaticity and intensity data for each color component.

1 5. The method of Claim 2, wherein the RGB-to-RGB mapping incorporates
2 chromaticity and intensity data for each color component.

1 6. A color management system for converting computer graphics images to film
2 images, the computer graphics images being displayed on and manipulated using a computer
3 monitor, the film images being recorded on film using a digital film recorder for exposing the
4 film with light at predetermined intensity levels corresponding to specified RGB values,
5 comprising:

6 a first RGB-to-XYZ mapping applicable to the monitor, said first RGB-to-XYZ
7 mapping using color spaces incorporating chromaticity and intensity data for each color
8 component;

9 a second RGB-to-XYZ mapping applicable to the film recording, said second RGB-
10 to-XYZ mapping using color spaces incorporating chromaticity and intensity data for each
11 color component; and

12 an RGB-to-RGB mapping, incorporating chromaticity and intensity data for each
13 color component, for operating on the image colors displayed on the monitor to create
14 accurate color densities on the film.

1 7. A color management system for converting color computer graphics images to
2 color film images, comprising:

3 a computer system having a monitor for displaying the computer graphics images;
4 an RGB-to-XYZ mapping, incorporating chromaticity and intensity data, for the
5 monitor;

6 an RGB-to-XYZ mapping, incorporating chromaticity and intensity data, applicable to
7 recording the film images;

8 an RGB-to-RGB mapping, incorporating chromaticity and intensity data, for operating
9 on the images displayed on the monitor to create color components for recording the film
10 images

1 8. The system of Claim 7, wherein the computer system comprises a work station.

1 9. The computer system of Claim 7, further comprising a digital film recorder for
2 exposing film with the film images using light at predetermined intensity levels
3 corresponding to specified RGB values.

1 10. The computer system of Claim 7, wherein the RGB-to-XYZ mapping for the
2 monitor incorporates chromaticity and intensity data for each color component.

1 11. The computer system of Claim 7, herein the RGB-to-XYZ mapping for recording
2 the film images incorporates chromaticity and intensity data for each color component.

1 12. The computer system of Claim 7, wherein the RGB-to-RGB mapping
2 incorporates chromaticity and intensity data for each color component.

1/2




FIG. 1

SUBSTITUTE SHEET (RULE 26)

2/2




FIG. 2

INTERNATIONAL SEARCH REPORT

International Application No.

PCT/US 99/23981

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 G06T11/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 G06T

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	MACDONALD L W: "Developments in colour management systems" DISPLAYS, GB, ELSEVIER SCIENCE PUBLISHERS BV., BARKING, vol. 16, no. 4, 1 May 1996 (1996-05-01), pages 203-211, XP004032522 ISSN: 0141-9382 the whole document ---	1-12
X	US 5 754 184 A (RING STUART FREDERICK ET AL) 19 May 1998 (1998-05-19) abstract; claims 1-7 column 5, paragraphs 1-3 column 8, line 35 - line 44 --- -/--	1-12

☒ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"Z" document member of the same patent family

Date of the actual completion of the international search

28 January 2000

Date of mailing of the international search report

08/02/2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Filloy García, E

INTERNATIONAL SEARCH REPORT

Int. l. Application No
PCT/US 99/23981

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No
P,X	<p>RAMAMURTHY A ET AL: "ACHIEVING COLOR MATCH BETWEEN SCANNER, MONITOR, AND FILM: A COLOR MANAGEMENT IMPLEMENTATION FOR FEATURE ANIMATION"</p> <p>SMPTE JOURNAL.US.SMPTE INC. SCARSDALE, N.Y.,</p> <p>vol. 108, no. 6, June 1999 (1999-06),</p> <p>pages 363-373, XP000831862</p> <p>ISSN: 0036-1682</p> <p>page 364 -page 366; figure 1</p> <p style="text-align: center;">---</p>	1-12
Y	<p>WO 95 31794 A (APPLE COMPUTERS INC ;SWEN IUE NA STEVE (US); STOKES MICHAEL D (US))</p> <p>23 November 1995 (1995-11-23)</p> <p>page 9, line 3 - line 13; figure 7</p> <p>page 17, paragraphs 3,4</p> <p style="text-align: center;">---</p>	1-12
Y	<p>EP 0 814 603 A (KONISHIROKU PHOTO IND)</p> <p>29 December 1997 (1997-12-29)</p> <p>claims 1,7-9,12,15; figure 1</p> <p>page 12, line 41 -page 13, line 2</p> <p style="text-align: center;">---</p>	1-12
A	<p>K. JIN-SEO ET AL: "Development of Color Management System Prototype"</p> <p>PROCEEDINGS OF THE 1998 IEEE INTERNATIONAL CONFERENCE ON SYSTEMS, MAN, AND CYBERNETICS,</p> <p>vol. 3, 11 - 14 October 1998, pages 2529-2532, XP000874180</p> <p>San Diego, USA</p> <p>abstract: page 2530, section 3</p> <p style="text-align: center;">---</p>	1-12
A	<p>US 4 979 032 A (GIORGIANNI EDWARD J ET AL) 18 December 1990 (1990-12-18)</p> <p>abstract: figure 1</p> <p style="text-align: center;">---</p>	1-12
A	<p>EP 0 637 731 A (TOYOTA MOTOR CO LTD)</p> <p>8 February 1995 (1995-02-08)</p> <p>abstract: claims 1-3</p> <p style="text-align: center;">-----</p>	1-12

INTERNATIONAL SEARCH REPORT

information on patent family members

International Application No
PCT/US 99/23981

Patent document cited in search report	Publication date	Patent family member(s)	Publicatio date
US 5754184 A	19-05-1998	NONE	
WO 9531794 A	23-11-1995	AU 2640095 A	05-12-
EP 0814603 A	29-12-1997	JP 10075377 A US 5966505 A	17-03- 12-10-
US 4979032 A	18-12-1990	NONE	
EP 0637731 A	08-02-1995	JP 7050760 A JP 2921365 B JP 7150081 A DE 69414323 D DE 69414323 T EP 0822396 A US 5590251 A	21-02- 19-07- 13-06- 10-12- 27-05- 04-02- 31-12-

THIS PAGE BLANK (USPTO,

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☒ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☒ FADED TEXT OR DRAWING
- ☒ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.

THIS PAGE BLANK (USPTO)